

PIEMATE RESILIENT WEDGE GATE VALVE

COMPLETE WITH BYPASS VALVE PN10 OR PN16, DN450-DN600

INTRODUCTION

PIEMATE Resilient Seat Wedge Gate Valve, exceeds the requirements of BS 5163 Type B. Suitable for use with water and neutral liquids, to a maximum temperature of 80 deg-celsius.



FEATURES & BENEFITS

- * Unique Ductile Iron Wedge design provide strength and sealing efficiently.
- * Low operating torques, no gearing is needed and smaller electrical actuators are sufficient for optimum, effective and cost saving valve operations.
- * Wedge fully encapsulated in NBR or EPDM.
- * Stem nut permit individual removal conforming to BS 5163 requirement.
- * Triple independant O-ring stem seals ensure watertight sealing and longer life.
- * O-ring stem seals replaceable under full pressure conditions.
- * Fusion Bonded Epoxy (FBE) Coating.
- * Clear full bore for optimum flow and under pressure tapping.
- * Valve to close clockwise unless otherwise specified.



PIEMATE SDN.BHD. (106977-A)

No.28, (Lot 17512), Jalan Dua, Kawasan Perindustrian Selayang,
Taman Selayang Baru, 68100, Selangor Darul Ehsan, Malaysia.
Tel: 603-61380977, 61388667 Fax: 603-61388772 e-mail: pipemate@tm.net.my

